

Horizon 7600

Omnidirectional Laser Scanner

Honeywell's Horizon® 7600 is a compact in-counter hands-free laser scanner designed with a dense 20-line scan pattern that provides fast, efficient throughput.

Horizon is equipped with an integrated RF EAS deactivation antenna. The EAS security tag, designed to reduce shrink, is deactivated and the bar code is scanned with a single pass. These simultaneous operations help improve operator comfort and increase throughput. To further enhance operator efficiency and productivity, Horizon is equipped with IR laser activation. This allows the user to "wake" the unit from a power save or sleep mode and read a bar code instantaneously.

Each Horizon includes an RS232 auxiliary port that allows for hand-held bar code scanners to be connected providing easy scanning of bulky, oversized objects. Other peripherals such as check readers or magnetic stripe readers can also utilize the flexibility of the auxiliary port. The Horizon also provides multiple interfaces and data parsing making it compatible with almost every POS system on the market today.

The combination of performance, ruggedness, and a myriad of features make the Horizon an ideal choice for grocery, supermarket, retail, package depot, and a multitude of other applications.



Features

- **Durable Die-Cast Construction:** Withstands abuse in the harshest environments
- **Flash ROM:** Protects POS investment with free firmware updates via MetroSet®2 software and standard PC
- **Built In RF EAS Antenna:** Increases efficiency by simultaneously deactivating RF EAS tags and decoding bar codes
- **Field Replaceable Window:** Fast repairs without removing unit from service
- **Auxiliary Port:** Connect an external scanner or other peripheral directly to the scanner

Horizon 7600 Technical Specifications

Mechanical

| | |
|--------------------|--|
| Dimensions (LxWxH) | 88 mm x 229 mm x 193 mm (3.5" x 9.0" x 7.6") |
| Weight | 2.9 kg (6.3 lbs) |

Electrical

| | |
|------------------------|--|
| Input Voltage | 5 VDC \pm 0.25 V |
| Operating Power | 2.6 W (500 mA @ 5 V) |
| Standby Power | 830 mW (<165 mA @ 5 V) |
| Host System Interfaces | USB, RS232, Keyboard Wedge, IBM 46xx (RS485), OCIA, Laser Wand Emulation |
| Auxiliary Ports | RS232: Secondary Scanner or Scale, EAS |

Environmental

| | |
|-----------------------|--|
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Storage Temperature | -40°C to 60°C (-40°F to 140°F) |
| Humidity | 5% to 95% relative humidity, non-condensing |
| Environmental Sealing | Sealed to resist airborne particulate contaminants |
| Light Levels | 4842 Lux |

Scan Performance

| | |
|-------------------|---|
| Scan Pattern | Omnidirectional: 5 fields of 4 parallel lines |
| Scan Speed | 2000 scan lines per second |
| Print Contrast | 35% minimum reflectance difference |
| Pitch, Skew | 60°, 60° |
| Decode Capability | Reads standard 1D and GS1 DataBar symbologies |
| Warranty | 3 year factory warranty |

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance
 For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies



For more information:
www.honeywellaidc.com

| Typical Performance* | |
|----------------------|---------------------------|
| Narrow Width | Depth of Field |
| 5.2 mil | 0 mm - 38 mm (0" - 1.5") |
| 7.5 mil | 0 mm - 114 mm (0" - 4.5") |
| 10.4 mil | 0 mm - 178 mm (0" - 7.0") |
| 13 mil | 0 mm - 203 mm (0" - 8.0") |
| 19 mil | 0 mm - 229 mm (0" - 9.0") |

*Resolution: 5 mil (0.125 mm)
 *Performance may be impacted by bar code quality and environmental conditions

Honeywell Scanning & Mobility

9680 Old Bailes Road
 Fort Mill, SC 29707
 800.582.4263
www.honeywell.com

Honeywell



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

