star DP8340



Typical Applications

- Receipt Printer
- Mobile Printing
- Data Terminals
- Test Equipment Results
- Weights and Measures (Scale)



Hospitality



Kitchen

Versatile, Wide, Mobile Compact Receipt Printer

The DP8340 is a unique 114mm wide dot matrix impact printer used all around the world in multiple applications. The wide width allows it to print reports, receipts or invoices depending on your needs. Its ability to be powered by 12V in addition to its high reliability, make it a perfect product for mobile applications in vehicles. Special items on the receipt can be easily identified due to the printers red print feature.

Visit www.starmicronics.com to learn more.

Product Range

- DP8340FC Tear Bar, Parallel, 4.5" Paper Width
- DP8340FM Tear Bar, RJ-45 Serial, 4.5" Paper Width
- DP8340RC Tear Bar, Parallel, 3.25" Paper Width
- DP8340RM Tear Bar, RJ-45 Serial, 32.5" Paper Width
- DP8340SC Tear Bar, Parallel, 4.5" Paper Width, Sprocket Version
- DP8340SM Tear Bar, RJ-45 Serial, 4.5" Paper Width, Sprocket Version



Wide Format



Black & Red Printing









DP8340 Specifications

	The Original Ultra Reliable POS Printer!	
Features	Hardware Ultra Reliable Receipt Printer 2 LPS (Lines per Second) Small Footprint Wide Format 4.5" Model Standard 3.25" Model Sprocket Model	40 / 60 Column 9-Pin Print Head 12 VDC (Ideal for Mobile Applications)
Connectivity Note: Connections in bold are supported; grayed-out connection types may be supported by special request.	RJ-45 Serial 25-Pin Serial Parallel USB Powered USB Ethernet WiFi Dual 9-Pin Serial/USB	Virtual Serial Port to USB Virtual Serial Port to Ethernet Virtual TCP/IP Port
Drivers	Windows® XP Vista (32 bit / 64 bit) Windows 7 (32 bit / 64 bit) Server 2008 (32 bit / 64 bit) CE XP Embedded POS for .NET	OPOS™ JavaPOS™ StarlO SDK
What's Included	User Manual Paper Holders Re-Roll Prevention Guard Ribbon Cartridge DIP Switch Cover	
Optional Accessories	External Power Supply (PS8340) Automotive 12V Power Adapter	Ribbons: SF-01B – Black SF-03BR – Black/Red
Models	DP8340FM RJ-45 Modular Jack Serial I/F, 4.5" Roll Paper DP8340RM RJ-45 Modular Jack Serial I/F, 3.25" Roll Paper DP8340FC Parallel I/F, 4.5" Roll Paper DP8340RC Parallel I/F, 3.25" Roll Paper DP8340SM RJ-45 Modular Jack Serial I/F, 4.5" Sprocket Paper DP8340SC Parallel I/F, 4.5" Sprocket Paper	
Technical Specifications	Print Method : 9 Pin Impact Dot Matrix Print Speed : 2 LPS (Lines per Second) Paper Width : 82.5mm to 114.3mm Paper Thickness : 0.07 - 0.09mm Paper Diameter : Max 80mm Emulation : Star DP8340	Power: 12VDC MCBF: 10 Million Lines Dimensions: W=202mm, H=98mm, D=200mm
Warranty	For US and Canada: 3-Year Limited Warranty	
For Further Information	Sales:1-800-782-7636 x107Technical Support:1-800-782-7636 x105	Web: http://www.starmicronics.com
		2/25/10



Star Micronics America, Inc. • 1-800-782-7636 x107 • www.starmicronics.com ©2010 Star Micronics America, Inc. All Rights Reserved. All trademarks are property of their respective owners. Specifications are subject to change without notice.



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

Get in touch with us on social media!

www.L-Tron.com