



DU-5K-TP2

DESKTOP KEYBOARD WITH TOUCHPAD

The DU-5K-TP2 features an integrated Cirque extended temperature touchpad pointing device, with left and right-click mouse buttons underneath for additional ease of use. It is designed to meet NEMA 4X specifications. It has 116-key functionality, including 24 function keys. The mounting holes on the back further increase the unit's versatility.

Features:

24 Function Keys

Polycarbonate Case with Mounting Holes

USB and PS/2 configurations available

Product Code DU-5K-TP2

| | |
|-------------------|--|
| CERTIFICATIONS | NEMA 4X UL60950, FCC Part 15 Class B, IP65 |
| SHOCK | 3x11 ms pulses of 50g on each of 3 axes |
| CABLE | LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 Cable (providing separate keyboard and mouse connections) |
| KEY SWITCH | MATERIAL: Industrial silicone rubber LIFE: Greater Than 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 6.35 oz +/- 1.06 oz (180g +/- 30g) FEEDBACK: Tactile with mechanical snap |
| VIBRATION | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours |
| POWER | PS2: KEYBOARD: 50mA@5V (from Keyboard port) TOUCHPAD: 10mA@5V (from Mouse port) USB: 60mA@5V (from CPU port) |
| COMPATIBILITY | PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems USB KEYBOARD/TOUCHPAD: All Windows and Macintosh OS |
| TEMPERATURE RANGE | STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F) |
| WEIGHT | 2.25 lbs +/- 0.10 lbs (1.02 kg +/- 0.05 kg) |
| WARRANTY | 1 year limited warranty |
| HUMIDITY | 100% |
| DIMENSIONS | 14.94" x 6.63" x 1.81" (w-h-d) 379.5mm x 168.1mm x 45.9mm |
| MODEL NUMBERS | DU-5K-TP2-PS2: With PS/2 cable DU-5K-TP2-USB: With single USB cable |



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

