



## PMU-1000

## PANEL MOUNT KEYBOARD

iKey's rugged panel mount keyboards allow for easy integration into workstations or other industrial environments. They are designed to meet NEMA 4X specifications, enabling them to withstand the roughest of conditions.

## Features:

10-Key Numeric Pad 104-Key Functionality

12 Function Keys

USB, PS/2 and AT/serial configurations available

## Product Code PMU-1000

CERTIFICATIONS	NEMA 4X, CE UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10' Straight (3 m)
KEY SWITCH	MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in.
	(1.4mm) ACTUATION FORCE: 6.35 oz +/- 1.06 oz. (180g +/- 30g) FEEDBACK: Tactile with
	Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST
	PER AXIS: 3 hours
POWER	PS2 or AT: 50mA@5V (from Keyboard port) USB: 50mA@5V (from CPU port)
COMPATIBILITY	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All
	Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
WEIGHT	2.00 lbs +/- 0.10 lbs (0.91 kg +/- 0.05 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100%
DIMENSIONS	15.39" x 7.06" x 1.25" (w-h-d) 390.9mm x 179.3mm x 31.8mm CUTPIT: 13.52" x 5.18" (w-h) 343.4mm
	x 131.6mm
MODEL NUMBERS	PMU-1K-PS2 PMU-1K-STD PMU-1K-USB



www.L-TronDirect.com 800-830-9523 info@L-Tron.com

