

PMU-5K-TP2

PANEL MOUNT KEYBOARD WITH TOUCHPAD



iKey's rugged panel mount keyboards allow for easy integration into workstations or other industrial environments. The PMU-5K-TP2 combines a Cirque extended temperature touchpad with left and right-click buttons underneath and a 10-key numeric keypad to provide dual functionality in one compact unit. Its 24 function keys provide user versatility. This keyboard also offers user Windows keys for ease of access to the operating system.

Features:

- 10-Key Numeric Pad
- 24 Function Keys
- ABS Polycarbonate Frame with 8-32 Mounting Studs
- Integrated Touchpad
- MS Windows™ Function Keys
- USB and PS/2 configurations available

Product Code PMU-5K-TP2

CERTIFICATIONS	NEMA 4X, CE UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 (providing separate keyboard and mouse connections) MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in.
KEY SWITCH	(1.4mm) ACTUATION FORCE: 6.35 oz. +/- 1.06 oz. (180g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS2: KEYBOARD: 50mA@5V (from Keyboard port) POINTER: 10mA@5V (from Mouse port) USB: 60mA@5V (from CPU port)
COMPATIBILITY	PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
WEIGHT	2.00 lbs +/- 0.10 lbs (0.91 kg +/- 0.05 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	15.39" x 7.06" x 0.50" (w-h-d) 390.9mm x 179.3mm x 12.7mm SCREWS: 0.75" (19.1mm) CUTPIT: 13.52" x 5.18" (w-h) 343.4mm x 131.6mm
MODEL NUMBERS	PMU-5K-TP2-PS2: With PS/2 cable PMU-5K-TP2-USB: With USB cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

