

RDC-3000

RACKDRAWER KEYBOARD WITH POINTING DEVICE



Ruggedized rackdrawer keyboards from iKey corner the market on rackmount peripherals. The RDC-3000 offers the benefit of an integrated ruggedized HulaPoint™ pointing device. Standard size units have 14-inch rails (15-inch-deep drawer) and come with chrome handle or pull slot options. Larger size units have 16-inch rails (17-inch drawer) and come with T-handle or locking T-handle options. The drawers have a CRS steel construction, which is coated with black epoxy paint, and chrome-plated, ball-bearing slides. (Model shown in photo is the T-handle option, part number RDC-3000-16-T)

Features:

Integrated HulaPoint™ Pointing Device
Slide Load Rating: 130 Lbs/Pair
USB, PS/2 and AT/serial configurations available

Product Code RDC-3000

CERTIFICATIONS	NEMA 12 UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 or AT/serial Cable (providing separate keyboard and mouse connections)
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 ACTUATION FORCE: 200g (+/- 20g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	KEYBOARD: 5V@ 10 ma (from CPU port) HULAPOINT: 5V@ 10 ma (from mouse conn. port)
COMPATABILITY	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to 194F) OPERATING: -40C to +70C (-40F to 158F)
WEIGHT	16 lbs (7.36 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100%
DIMENSIONS	Pull Slot/Chrome Handle: 19" x 15" x 1U (1.75") (w-h-d) 482.6mm x 381mm x 44.5mm T-handle: 19" x 17" x 1U (1.75") 482.6mm x 431.8mm x 44.5mm
MODEL NUMBERS	RDC-3000-PS2: With PS/2 cable RDC-3000-STD: With AT/serial cable RDC-3000-16-T-xxx: 16" Rails T-Handle RDC-3000-16-RK-xxx: 16" Rails T-Handle with Key



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

