



SL-86-911-TP-FL

MOUNTABLE KEYBOARD WITH TOUCHPAD

The SL-86-911-TP-FL keyboard is designed for in-vehicle use for emergency, police, service, transport trucks and marine vessels. Its thinner depth dimension of 1.125 inches allows it to fit easily into existing mounts. Features include a user-friendly integrated touchpad, backlit keys for low-light environments, a one-touch emergency key. The new, easy-to-use integrated touchpad was created to meet public demand for a user-friendly alternative to the traditional HulaPoint™ pointing device.

Features:

86-Key Functionality
Fn Key for Secondary Legend Flexibility
Integrated Touchpad
Meets NEMA 4X (IP65) Specifications
One-Touch Emergency Key
Red Backlit Keys

Product Code SL-86-911-TP-FL

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 4 ft coiled (1.2m) DESIGN: "Y" PS/2 (providing separate keyboard and mouse connections),
	or Single-Cable USB
KEY SWITCH	MATERIAL: Industrial Silicone rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. (1.4mm)
	ACTUATION FORCE: 7.05 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2kHz DURATION OF TEST
	PER AXIS: 3 hours
POWER	KEYBOARD: 200mA@5V (from Keyboard port) TOUCHPAD: 10mA@5V (from mouse port) USB:
	210mA@5V (from CPU port)
FLAMMABILITY	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO
COMPATABILITY	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All
	Windows and Macintosh OS
TEMPERATURE RANGE	Storage -40C to +90C (-40F to +194F) Operating -40C to +70C (-40F to +158F)
WEIGHT	2 lbs +/- 0.10 lbs (1.38 kg +/- 0.05 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100%
DIMENSIONS	12.0" x 7.74" x 1.27" (w-h-d) 304.8mm x 196.6mm x 32.3mm
MODEL NUMBERS	SL-86-911-TP-FL-PS2: With PS/2 cable SL-86-911-TP-FL-USB: With USB cable



www.L-TronDirect.com 800-830-9523 info@L-Tron.com

