



SL-88

COMPACT BACKLIT INDUSTRIAL KEYBOARD

The SL-88 is a waterproof and dustproof keyboard that is ideal for industrial, kiosk and mobile computing applications. Constructed in a small-footprint compact case, the SL-88 allows for space saving and mobility, while backlighting makes this keyboard functional in low-light environments. It is a versatile keyboard that offers a high-value solution for a low price. The SL-88 includes secondary legend accessed with NumLock and Fn key.

Features:

- 12 Function Keys
- 88-Key Functionality
- Polycarbonate Case with Mounting Holes
- Red Backlit Keys
- USB and PS/2 configurations available

Product Code SL-88

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 4 ft coiled (1.2m)
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz +/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS2: 200mA@5V (from Keyboard port) USB: 200mA@5V (from CPU port)
FLAMMABILITY	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO
COMPATABILITY	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (4-0F to +158F)
WEIGHT	2 lbs +/- 0.10 lbs (0.91 kg +/- 0.05 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100%
DIMENSIONS	11.40" x 6.30" x 1.86" (w-h-d) 285.8mm x 160mm x 47.2mm
MODEL NUMBERS	SL-88-PS2: With PS/2 cable SL-88-USB: With USB cable SL-88-STD: With AT cable



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

