

## SLK-102-461

### IKEY'S SLIMKEY® SLK-102-461



Designed to meet MIL-STD-461 standards, iKey's SlimKey® SLK-102-461 is ideal for harsh environments where electromagnetic interference is a top concern. In addition the SLK-102-461 provides full-size versatility in a rugged, compact design, with the added convenience of an integrated HulaPoint II®. The SlimKey® SLK-102-461 is engineered to meet NEMA 4X specifications, and is resistant to sand, debris and the elements. The large numeric pad on the SLK-102-461 allows for easy data entry, while the robust polycarbonate case is durable in the roughest of environments. Other features also include red LED backlit keys for nighttime use.

#### Features:

12 Function Keys

Designed to meet MIL-STD-461F Specifications

Military

Full-Size

Integrated HulaPointII™ Pointing Device

### Product Code SLK-102-461

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3 x 11 ms pulses of 50g on each of 3 axes
KEY SWITCH	MATERIAL: Industrial Silicone Rubber LIFE: Greater Than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06oz (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: .04G/hz FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
COMPATABILITY	Ps/2 KEYBOARD/HULAPOINT: All Windows Operating Systems
TEMPERATURE RANGE	STORAGE: -40F to 194F (-40C to +90C) OPERATING: -40F to +158F (-40C to +70C)
WEIGHT	1.5 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)
WARRANTY	1 Year Limited Warranty
DIMENSIONS	5.55" x 14.60" x 1.05" (w-h-d) 141mm x 370.9mm x 26.7mm



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

