



SLP-101

FULL-SIZE PANEL MOUNT KEYBOARD WITH BACKLIGHTING

iKey's SlimKey™ SLP-101 panel mount keyboard provides full-size versatility in a rugged, compact design. It features red LED backlighting for low-light environments. When properly installed, the SlimKey™ SLP-101 is engineered for NEMA 4X protection from dust, water and corrosive liquids. It is designed for easy integration into workstations, kiosks and industrial environments. The large numeric pad on the SLP-101 allows for easy data entry, while the robust polycarbonate case stands up in the roughest of conditions.

Product Code SLP-101

| | |
|-------------------|---|
| Certifications | NEMA 4X, CE UL 60950, FCC Part 15 Class B |
| Shock | 3 X 11 ms pulses of 50g on each of 3 axes |
| Cable | LENGTH: 10' straight (3 m) DESIGN: "Y" PS/2 or USB Cable |
| Key Switch | MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap |
| Vibration | Vibration POWER SPECTRAL DENSITY: .04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours |
| Power | PS2: 210mA@5V (from Keyboard port) USB: 210mA@5V (from CPU port) |
| Compatibility | PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS |
| Temperature Range | STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F) |
| Weight | 1.50 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg) |
| Warranty | 1 Year Limited Warranty |
| Humidity | 100% Humidity Resistant |
| Dimensions | 15.10" x 6.05" x 0.58" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h) 348mm x 118.1mm |
| Model Number | SLP-101-PS2: With PS/2 cable SLP-101-USB: With USB cable |



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

Get in touch with us
on social media!

