

## SLP-86-911

### PANEL MOUNT KEYBOARD WITH EMERGENCY KEY



The SL-86-911 offers both a rugged keyboard and rugged computer pointing device in one compact package. Ideal for mobile applications, it introduces a specially designed emergency key that, when pressed, sends a signal of Shift+F1 and lights up for 30 seconds. The SL-86-911 integrates the HulaPoint II™, an upgraded pointing device that offers improved sensitivity and increased durability. It boasts a completely sealed and ruggedized construction that, when properly sealed, allows it to meet NEMA 4X specifications, ensuring that this keyboard is sealed against the elements or unwanted spills. The SL-86-911 is now available with a single USB cable.

- Features:
- 12 Function Keys
  - 86-Key Functionality
  - Integrated Backlighting
  - Integrated HulaPoint II™ Pointing Device
  - One-Touch Emergency Key
  - USB and PS/2 configurations available

### Product Code SLP-86-911

|                   |  |
|-------------------|--|
| Certifications    | NEMA 4X, CE UL60950, FCC Part 15 Class B   |
| Shock             | 3x11 ns pulses of 50g on each of 3 axis  |
| CABLE             | LENGTH: 4 feet (1.2 meters) DESIGN: "Y" PS/2 Cable (providing separate keyboard and mouse connections), or Single-Cable USB  |
| Key Switch        | MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap |
| Vibration         | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours  |
| Power             | PS2: KEYBOARD: 200mA@5V (from Keyboard port) POINTER: 35mA@5V (from Mouse port) USB: 235mA@5V (from CPU port)  |
| FLAMMABILITY      | PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO  |
| Compatibility     | PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS  |
| Temperature Range | STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F)   |
| Weight            | 1 year limited warranty  |
| Warranty          | 1 Year Limited Warranty  |
| Humidity          | 100% Humidity Resistant  |
| Dimensions        | 11.80" x 6.79" x 1.35" (w-h-d) 299.7mm x 172.5mm x 34.3mm CUTOUT: 10.40" x 5.40" (w-h) 264.2mm x 137.2   |





[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

Get in touch with us  
on social media!

