



SEE MORE. DO MORE.

# Specification Sheet

## 8000T Cling

### Features:

- Thermal transfer, vinyl static cling label
- Recommended for labeling applications requiring clean removability
- Available in white (66741RM)
- May be used in desktop printers
- For best performance use 3200 ribbon

### Suggested Applications:

- Oil Change labeling
- Temporary parking identification
- Window labeling
- Work in process labeling

### Material Construction:

	Description	Caliper
Facestock	White topcoated cling vinyl film	6.0 mil
Liner	40 lb. semi-bleached, kraft stock	2.5 mil
<b>Total</b>		8.5 mil +/- 10%

### Temperature Performance:

- Minimum Application Temperature: 32° F (0° C)
- Service Temperature: -40° F to 200° F (-40° C to 93° C)
- Storage Conditions: 32° F to 70° F (0° C to 21° C) at 35% to 50% RH
- Expected Exterior Life: Two years

**Suggested Ribbons for Applications with Chemicals**

Ribbon	Relevant Automotive Chemicals					
	Windex	Windshield Washer Fluid	Antifreeze	Motor Oil	Gasoline (Soak)	Gasoline (Rub)
<b>3200 (for 8000T Cling White)</b>	X	X	X	X	X	

X indicates acceptable performance

**Product Performance and Suitability**

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.



[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

