

# SYMBOL DS7708

## Easy to deploy high-performance “can’t miss” on-counter scanning

When it comes to on-counter scanning, the DS7708 offers a feature set that puts it at the top of its class for performance, ease of deployment and total cost of ownership. No matter what bar codes appear at your POS, the DS7708 can scan them all — 1D, 2D, printed and electronic — as fast as your cashiers can slide items past the scan window. With its compact design, the DS7708 can easily be installed in even the most space constrained checkout lanes. And extraordinary durability minimizes costs and protects uptime, maximizing device lifecycle and your return on investment.



### Scan virtually any bar code, in any condition, on any medium

First-time every time capture of 1D and 2D bar codes displayed on mobile devices or printed on paper labels — even if they are damaged, poorly printed or dirty.

### PRZM Intelligent Imaging technology for next generation scanning performance

Resets the bar for 2D imaging by improving decode performance and snappiness, dramatically improving the user experience, user productivity, throughput and customer wait times.

### Next generation swipe speeds up to 100 in./2.5 m per second

Enables users to capture bar codes as fast as they can pass items in front of the scan window.

### Largest field of view and omni-directional scanning for can’t-miss “swipe-and-go” scanning simplicity

A field of view that is over 50 percent larger than competitive 2D imagers enables easy capture of bar codes, regardless of where they are located on an item. Scanning is truly second nature — no need to orient an item to capture the bar code.

### Superior durability

Multiple features make the DS7708 the most durable device in its class. The recessed scan window prevents marks and scratches that can degrade scanning performance and lifecycle. In addition, the electronics are located in the top area of the DS7708 to prevent damage and protect uptime in the event of a spill.

### Virtually invisible illumination

The LEDs are recessed behind the scan window, where they are barely visible and won’t disturb customers or cashiers.

### Integrated Checkpoint EAS

Scan bar codes and deactivate EAS tags in a single motion, improving cashier productivity and protecting the shopping experience by preventing embarrassment for customers who inadvertently set off an alarm when exiting the store with an active EAS tag.

### Power through a single USB port

No additional power supply is required when connecting via USB, reducing accessory, installation and management costs.

### Easily add a handheld scanner

Do cashiers need a handheld scanner for the flexibility to scan large items in the cart? A standard USB port provides plug-in-and-go simplicity for a wide variety of auxiliary scanners.

### Image capture support expands functionality and increases value

The DS7708 offers additional data capture features to further streamline your business processes. For example, workers can take a picture of a check, driver’s license or ID card to meet store requirements or industry regulations in a split second, protecting cashier productivity and throughput in the checkout line.

### Superior out-of-box experience

Smart auto-host detect cables automatically determine which interface is attached, eliminating the need to scan numerous configuration bar codes. Over 90 international keyboards are supported, enabling easy setup, all around the world.

PROTECT SALES AND CUSTOMER SERVICE WITH THE POWER TO RING UP PURCHASES FASTER THAN EVER WITH THE DS7708. FOR MORE INFORMATION, VISIT [WWW.ZEBRA.COM/DS7708](http://WWW.ZEBRA.COM/DS7708) OR ACCESS OUR GLOBAL CONTACT DIRECTORY AT [WWW.ZEBRA.COM/CONTACTUS](http://WWW.ZEBRA.COM/CONTACTUS)

## Specifications

For a complete list of specifications, including regulatory information and decode ranges, please visit [www.zebra.com/ds7708](http://www.zebra.com/ds7708)

PHYSICAL CHARACTERISTICS	
<b>Dimensions</b>	Scanner only: 5.63 in. H x 5.86 in. W x 3.81 in. D 14.3 cm H x 14.9 cm W x 9.7 cm D  Scanner with Table Mount Kit: 6.06 in. H x 5.93 in. W x 3.85 in. D 15.4 cm H x 15.1 cm W x 9.8 cm D
<b>Weight</b>	17.6 oz. / 500 g
<b>Voltage and Current</b>	Without auxiliary scanner: Standby: 5 VDC +/-10% @ 125ma avg. Operating: 5 VDC +/-10% @ 480ma avg.  With auxiliary scanner: Standby: 12 VDC +/-10% @ 100ma avg. Operating: 12 VDC +/-10% @ 400ma avg.
<b>Color</b>	Midnight Black
<b>Supported Host Interfaces</b>	USB, RS-232, Keyboard Wedge, TGCS (IBM) 46XX over RS485
<b>Keyboard Support</b>	Supports over 90 international keyboards
<b>Auxiliary Scanner Interface</b>	USB
<b>Electronic Article Surveillance</b>	Compatible with Checkpoint EAS deactivation systems
PERFORMANCE CHARACTERISTICS	
<b>Swipe Speed</b>	Up to 100 in./sec. (254 cm/sec.)
<b>Light Source</b>	Two deep red LEDs (660nm)
<b>Imager Field of View</b>	48.0° x 36.7° (bar-code reading) 48.0° x 33.7° (image capture)
<b>Image Sensor</b>	1280 x 960 (bar-code reading) 1280 x 880 (image capture)
<b>Minimum Print Contrast</b>	25% minimum reflective difference
<b>Roll / Pitch / Yaw (Skew)</b>	360°, ±70°, ±70° typical

USER ENVIRONMENT	
<b>Operating Temperature</b>	32° to 104° F / 0° to 40° C
<b>Storage Temperature</b>	-40° to 158° F / -40° to 70° C
<b>Humidity</b>	5% to 85% RH, non-condensing
<b>Environmental Sealing</b>	IP52
<b>Electrostatic Discharge (ESD)</b>	ESD per EN61000-4-2; +/- 25 KV Air Direct; +/- 8 KV Indirect (without auxiliary scanner)
<b>Ambient Light Range</b>	From darkness (0 fcd) to 450 fcd artificial light and 10,000 fcd direct sunlight

SYMBOLGY DECODE CAPABILITY	
Code 39, Code 128, Code 93, Codabar/NW7, Code 11, MSI Plessey, UPC/EAN, I 2 of 5, Korean 3 of 5, GS1 DataBar, Base 32 (Italian Pharma), PDF417, Micro PDF417, Composite Codes, TLC-39, Aztec, DataMatrix, MaxiCode, QR Code, Micro QR, Chinese Sensible (Han Xin), Postal Codes <i>Refer to Product reference Guide for complete list of symbolgies.</i>	

MINIMAL ELEMENT RESOLUTION	
Code 39 – 3 mil, UPC – 7.8 mil, PDF417 – 4 mil, Datamatrix – 7.5 mil, QR Code – 7.5 mil	

DECODE RANGES (TYPICAL)	
Code 39 – 5 mil:	0 – 7.2 in. (0 – 18.3 cm)
UPC/EAN – 10 mil (80%):	0 – 10.0 in. (0 – 25.4 cm)
UPC/EAN – 13 mil (100%):	0 – 10.3 in. (0 – 26.1 cm)
PDF417 – 5 mil:	0 – 3.5 in. (0 – 8.9 cm)
Datamatrix – 10 mil:	0 – 5.0 in. (0 – 12.7 cm)
QR Code – 10 mil:	0 – 4.9 in. (0 – 12.4 cm)

WARRANTY	
Subject to the terms of Zebra's hardware warranty statement, the DS7708 is warranted against defects in workmanship and materials for a period of 3 years from the date of shipment. Complete Zebra hardware product warranty statement: <a href="http://www.zebra.com/warranty">www.zebra.com/warranty</a>	

RECOMMENDED CUSTOMER SERVICES	
Service from the Start Advance Exchange Support	

## Complimentary Management Tools

<b>123Scan2</b> Programs scanner parameters, upgrades firmware, provides scanned bar code data and prints reports. <a href="http://www.zebra.com/123Scan">www.zebra.com/123Scan</a>	<b>Scanner Management Service (SMS)</b> Remotely manages your Zebra scanner and queries its asset information. <a href="http://www.zebra.com/sms">www.zebra.com/sms</a>	<b>Scanner SDK</b> Generates a fully-featured scanner application, including documentation, drivers, test utilities and sample source code. <a href="http://www.zebra.com/windowsSDK">www.zebra.com/windowsSDK</a>
---	---	--





[www.L-TronDirect.com](http://www.L-TronDirect.com)

800-830-9523

[info@L-Tron.com](mailto:info@L-Tron.com)

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

[www.L-Tron.com](http://www.L-Tron.com)

Get in touch with us  
on social media!

