



Industrial Thermal Printer



CL4NX™

SATO, Beyond Expectation

SATO's first truly UNIVERSAL Industrial Label Printer engineered for the most demanding printing applications

Simple-to-Operate



- Full Color Interactive LCD
- Videos that Offer Valuable Information on the Printer Operation
- Intuitive Menu Navigation
- Tool-less Maintenance

Plug-and-Play



- LTDS (Label Tension Damper System)
- Flexible Media Support - Use Wound In or Wound Out Media
- High Energy Mode - Prints on a Wide Variety of Stock Types

All-in-One



- Multiple Interfaces - Auto Switching
- Competitive Emulations On-board
- Multi-language Support



GENERAL SPECIFICATIONS / CL4NX™

PRINTER MODEL

CL4NX

PRINT SPECIFICATIONS

Print Method

Direct Thermal or Thermal Transfer

Print Resolution

203 dpi (8 dots/mm) 305 dpi (12 dots/mm) 609 dpi (24 dots/mm)

Print Speed

10 ips (254.0 mm/sec) 8 ips (203.2 mm/sec) 6 ips (152.4 mm/sec)

Print Mode

Continuous, Tear-off, Cutter, Dispense

Print Area

Maximum Width

4.1" (104.0 mm)

Maximum Length (Continuous mode)

98.43" (2500.0 mm) 59.06" (1500.0 mm) 15.75" (400.0 mm)

MEDIA SPECIFICATIONS

Sensor Type

Adjustable Transmissive Sensor for Gap, Adjustable Reflective Sensor for Black Mark, Paper End, Ribbon Near-End/End

Media Type

Roll (Continuous, Die-cut), Fan-fold, Tag, Ticket

Media

Width

0.87" (22.0 mm) - 5.04" (128.0 mm)

Thickness (label & liner)

0.002" (0.060 mm) - 0.011" (0.268 mm)

Roll Diameter

Maximum 8" (203.2 mm) on 3" (76.0 mm) ID Core
Optional 10" OD

Wind

Face-in / Face-out, No Setting Change Required

Ribbon

Width

1.55" (39.5 mm) - 5.04" (128.0 mm)

Length

1,968.5 ft (600 m) on 1" (25.4 mm) ID Core

Roll Diameter

Maximum 3.54" (90.0 mm)

Wind

Face-in / Face-out, No Setting Change Required

SATO Genuine Consumables

For Maximum Print Quality and Optimum Use, SATO Recommends The Use of SATO Genuine Consumables

MEMORY & PROCESSING SPECIFICATIONS

Dual CPU

CPU1: 2GB ROM, 256MB RAM
CPU2: 4MB ROM, 64 MB RAM

USER FRIENDLY SUPPORT TOOLS

Large Status LED

Blue/Red

Alarm Sound

Beep (3 volume setting)

Self Diagnosis

Head Check, Cutter-Cover Open, Stand-by mode, Auto-Calibration

Display Panel

3.5" Full Color LCD

Tool-less Maintenance

Print Head Replacement and Adjustment, Platen Replacement

Multi National Language Support

47 Languages Scalable Fonts for Print
31 Languages for LCD Menu

Operation Video

Multiple Instructional Videos On-board (e.g. Error Resolution, Media Loading, Parts Replacement and Cleaning)

Emulation

Auto detect - SBPL®, SZPL®, SDPL®, SIPL® or STCL®

Remote Maintenance

SNMP Ver. 3, HTTPS

COMMUNICATION INTERFACES SPECIFICATIONS

Standard

USB 2.0 (Type A, Type B), Ethernet (IPv4/IPv6) on Rear Panel
USB 2.0 (Type A) on Front Panel
RS-232C, IEEE1284, EXT on Standard Interface Board
Bluetooth® Ver.3.0 (only for NA & EU)

Optional Wireless LAN Kit (Internal)

Wi-Fi® Certified, CCX (Cisco®) version 4 Certified, IEEE 802.11 a/b/g/n, Dual Band (2.4 GHz, 5 GHz)

OPTIONS

Cutter, Dispenser with Internal Liner
Re-winder, Real-Time Clock, UHF RFID (ISO18000-6 Type C), W-LAN kit

FONT SPECIFICATIONS

Internal Fonts

Bitmap

U, S, M, WB, WL, XS, XU, XM, XB, XL, OCR-A, OCR-B, Chinese (GB18030, Big5), Korean (KSX1001)

Scalable

CG Times, CG Triumvirate™, 13 SATO Fonts - Unicode (47 Languages Supported)

BARCODE SYBLOGIES SPECIFICATIONS

Barcodes

Linear

Code 39, Code 93, Code 128, CODABAR (NW7), EAN8/13, GS1-Databar™, GS1-128 (UCC/EAN128), Interleaved 2/5, Industrial 2/5, JAN8/13, Matrix 2/5, MS1, Bookland, Postnet™, UPC-A/E

2D Symbolologies

PDF417, Micro PDF, Maxi Code, GS1 Data Matrix, QR Code, Micro QR Code and Composite Symbolologies

User Downloadable Fonts, Graphics or Format

Maximum 100MB

OPERATING & ENVIRONMENT CHARACTERISTICS

Electrical Requirements

Universal Auto-ranging Power Supply, 100-240VAC +/- 10%, 50/60Hz
Energy Star - Compliant

Standards & Certification

EN60950-1, UL60950-1/CSA C22.2 No.60950-1, C-Tick, CCC, KC, S-Mark

Agency Approvals

cMETus, CE marking, FCC, NEMKO GS, ICES-003, NMB-003, KC, CCC, S-mark,

Environment

Operating

32 to 104°F (0 to 40°C), 30 - 80% RH, Non-Condensing

Storage

-4 to 140°F (-20 to 60°C), 30 - 90% RH, Non-Condensing

PHYSICAL CHARACTERISTICS

Dimensions

Width: 10.67" (271.0 mm)
Depth: 17.99" (457.0 mm)
Height: 12.63" (321.0 mm)

Construction

Die-cast Aluminum (Base, Frame, Front Cover, Ribbon Spindle, Print Head Mechanism)

Side-cover

Bi-fold for Space Saving with Large Clear Window

Mounting Chassis

3 Fixtures for Flat or Incline Setting

Weight

33.0 lbs. (15.1kg)

SATO AMERICA, INC. CORPORATE

10350-A Nations Ford Rd
Charlotte, NC 28273
Phone: (704) 644-1650
Fax: (704) 644-1662
satosales@satoamerica.com

LABEL MANUFACTURING, SERVICE & SALES

UNITED STATES MEXICO CENTRAL AMERICA
CANADA CARIBBEAN

www.satoamerica.com/CL4NX

©2014 SATO America, Inc. All rights Reserved. Rev B • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

