

XT-5315



| | |
|----------------|--|
| Specification | XT-5315 |
| Processor | Intel G1820 / 2.7GHz / 2M Cache ; Intel G3320TE / 2.3GHz / 3M Cache ; Intel Core i3-4330TE / 2.4GHz / 4M Cache |
| System Memory | DDR3 1333 SO-DIMM x 2, max. 16GB, factory default: 4GB (DDR3 1333/1600 for Core i3 CPU) |
| Storage Device | SATA storage x 2 ; factory default: 320GB HDD x 1 |
| Power Supply | 12V DC power adaptor, 120W (Optional 150W when equipping with 2nd LCD display LM/TM-3014&LM/TM-3015) |
| OS Support | Windows 7 / POSReady 7 / Windows Embedded 8.1 Industry / Linux per request |

| | |
|-----------------------|--|
| Display | |
| LCD Display | 15" TFT LCD, 1024 x 768 resolution |
| Touch Function | True-flat Projected Capacitive Touch supporting 10 pts multi-touch |
| Brightness adjustment | By digital push button |

| | |
|-------------------|--|
| Connectivity | |
| LAN Port | 10 / 100 / 1000Mb x 2 |
| Serial Port | 6, DB9 x 2 + RJ45 x 2 on I/O plate, pin header x 2 from service window, 5V support on all COM ports, 12V support on COM 1 to COM 4 |
| UPS Port | Yes |
| Standard USB Port | 6, (2 x USB3.0 / 2.0 + 4 x USB2.0) |
| Powered USB Port | Optional 24V x 1 and 12V x 3 via GEN8E Base |
| Audio | Internal 2W speaker x 1 + Line-out |
| VGA Port | VGA x 1, 12V support for Posiflex monitors; mini-DP x 1 on service window |
| CR Port | 1, control 2 CR |

| | |
|-----------------------------|-------------------|
| Physical Dimension | |
| Dimension [W x D x H in mm] | 372 x 320 x 252.7 |
| Weight [N.W. in Kg] | 5.86 |

| | |
|---------------------|---|
| Environment | |
| Operation Condition | 0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD) |
| Storage Condition | -20°C - 70°C, 10%RH - 90%RH |

| | |
|-----------|---|
| Options | |
| SSD | SATA SSD |
| SA-105 | Side Attachment for XT Series with 3 track MSR |
| SA-205 | Side Attachment for XT Series with iButton |
| SA-305 | Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor |
| SA-405 | Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor |
| LM-3010 | 9.7" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface) |
| LM-3014 | 14" 1366 x 768 rear-mount wide screen 2nd display for XT Series (VGA interface) |
| LM-3015 | 15" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface) |
| LM-6607 | 7" 800 x 480 rear-mount 2nd display for XT series (USB interface) |
| PD-2608UE | 2 x 20 VFD, rear-mount, USB with Virtual COM support |
| PD-350UE | 2 x 20 LCD, rear-mount, USB with Virtual COM support |
| PD-6607 | 7" color LCD graphical line display, rear-mount (USB interface) |
| WiFi | Internal mini-PCIe WiFi module with PIFA Antenna |

*For complete listing of the optional attachments, please refer to the website.



Design and Manufacturing in Taiwan by Posiflex Technology Inc.

The product information and specifications are subject to change without prior notice.

2014Q3

Flexible! Powerful! Elegant!



XT-5315

High End Fan-free POS Terminal



POSIFLEX TECHNOLOGY INC.
 No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan
 Tel : +886-2-2299-1599 E-mail : sales@posiflex.com.tw
 Fax : +886-2-2299-1819 www.posiflex.com

Authorized Distributor / Reseller



In today's retail and hospitality market, POS terminal is no longer just a cold and hard business tool. It is a part of the store decoration, a part of the store image. Each curve and detail of the POS terminal should add something to the overall mood of the store, to lift the shopping experience of the customers.

With the true-flat PCAP touch screen supporting 10 points multi-touch, beautifully sculptured slim body, sexily curved base stand, Posiflex XT-5315 looks right at any elegantly decorated store. And more than just good looks, Posiflex XT-5315 is powerful enough to handle any task imaginable that comes its way.



Looks

Slimmer and sexier than ever, XT Series is a sharp departure from the traditionally more conservative Posiflex terminal design. Every curves and details are carefully thought out to make XT Series one of the most visually desirable terminals in the market.

Flexibility

XT-5315 comes with the selection of two foldable bases, the curvy slim GEN7E Base and the larger but practical GEN8E Base.

The new foldable bases allow XT-5315 to be configured into different configurations. "Flat Folded Mode" to save the shipping package volume. "Low Profile Mode" to allow greater interaction between cashier and the customers; and the traditional "Full Extended Mode". All this can be achieved with a simple pull of the hidden lever. This one terminal/multi-configurations concept provides unmatched flexibility to store owners and system integrators alike.



Full Extended Mode



Low Profile Mode



Flat Folded Mode



Performance

XT-5315 offer a wide range of performance options from Intel Celeron to Intel Core i3 that is powerful enough to process anything throw at it without even breaking a sweat.



Fan-free Design

Fan-free architecture of XT-5315 allow it to run on harsh environments, such as greasy kitchen, without ever worrying about the fan maintenance. It also allows the machine to run quietly, which is ideally suited for the high-end boutique stores or hospital environment.



GEN8E Base

Optional GEN8E Base that integrates internal power adaptor and Powered USB port into the base stand, which allows for clutter free counter.



www.L-TronDirect.com

800-830-9523

info@L-Tron.com

596 Fishers Station Dr | Victor, NY | 14564 | Suite 1 A

www.L-Tron.com

